



Ref: Spoke tension meter tabel

Customer: Centrimaster – 29/05/2012

Controller: Vanberlaer Johan

Meter n°: Centrimaster AWA 142582S (2)

Reading on instrument

Sapim spaken

kN	Kg	G14 dia. 2,00mm	G13 dia. 2,30mm	G13 Strong dia. 2.3 - 2.0 mm	Laser dia. 2.0 - 1,50 - 2.0 mm	Race dia. 2.0 - 1,80 - 2.0 mm	Sprint dia 2.0 - 1.7 - 2.0 mm	Force dia 2.18 - 1.8 - 2.0 mm
0.491	50	2.55	2.98	2.60	1.95	2.37	2.23	2.40
0.589	60	2.62	2.97	2.66	2.14	2.45	2.35	2.42
0.687	70	2.68	3.00	2.71	2.18	2.51	2.42	2.53
0.785	80	2.76	3.03	2.77	2.28	2.58	2.50	2.58
0.883	90	2.78	3.07	2.80	2.32	2.63	2.56	2.60
0.981	100	2.84	2.08	2.89	2.44	2.67	2.67	2.68
1.079	110	2.88	3.15	2.92	2.46	2.72	2.64	2.72
1.177	120	2.92	3.18	2.94	2.52	2.78	2.70	2.75
1.275	130	2.95	3.19	2.97	2.55	2.80	2.75	2.80
1.373	140	2.97	3.21	2.98	2.61	2.84	2.77	2.84
1.472	150	3.00	3.23	2.99	2.62	2.87	2.82	2.87
1.570	160	3.02	3.24	3.00	2.65	2.89	2.85	2.91
1.668	170	3.04	3.26	3.01	2.68	2.92	2.87	2.94
1.766	180	3.06	3.24	3.05	2.71	2.94	2.90	2.95
1.864	190	3.09	3.28	3.09	2.73	2.95	2.92	2.97
1.962	200	3.11	3.30	3.11	2.78	2.97	2.94	2.99

kN	Kg	CX Ray	CX	CX Speed	CX sprint	CX Force	D-Light	Super spoke
0.491	50	1.71	2.00	1.95	1.90	2.35	2.17	1.94
0.589	60	1.79	2.16	1.98	2.02	2.41	2.27	2.07
0.687	70	1.90	2.24	2.15	2.09	2.48	2.37	2.08
0.785	80	2.00	2.28	2.21	2.15	2.60	2.40	2.21
0.883	90	2.07	2.36	2.25	2.28	2.66	2.46	2.27
0.981	100	2.11	2.43	2.26	2.30	2.71	2.54	2.33
1.079	110	2.21	2.46	2.36	2.38	2.73	2.58	2.40
1.177	120	2.25	2.50	2.38	2.42	2.75	2.69	2.43
1.275	130	2.28	2.53	2.42	2.46	2.81	2.72	2.51
1.373	140	2.30	2.52	2.46	2.48	2.82	2.74	2.56
1.472	150	2.31	2.55	2.52	2.52	2.86	2.76	2.60
1.570	160	2.33	2.61	2.55	2.55	2.88	2.80	2.62
1.668	170	2.40	2.64	2.59	2.58	2.94	2.83	2.66
1.766	180	2.45	2.66	2.60	2.60	2.95	2.82	2.68
1.864	190	2.50	2.72	2.60	2.63	2.96	2.84	2.70
1.962	200	2.53	2.76	2.62	2.65	2.98	2.86	2.73

Tragen Sie hier den Wert ein gemessen mit dem beiliegenden Kalibrierstab.....

Fill in the value measured with the enclosed rod.....